

MATERIAL SAFETY DATA SHEET

FABRIC PROTECTOR

Identification

Product Name	"Fabric protector	UN Number:	1208
Shipping Name:	"Petroleum Products, lfp	Dangerous Goods Class:	3.1
		Poisons Schedule:	5
		Hazchem Code:	3YE
		Packaging Group:	II

N/A = Not applicable

Use: Protective Coating to Textiles

Physical Description/Properties

Appearance:	clear colourless liquid
Boiling Point: (Deg.C)	61-70
Vapour Pressure:	125mmHg@ 15 Deg C.
Specific Gravity: (at 25 deg)	0.68
Solubility in Water:	immiscible
Flammability Limits:	1.2% v/v- 7.5%v/v Lel Uel
pH as is	N/A
Flash Point:	-30 Deg C

Ingredients

Ingredient	CAS No	
Mixture of Liquid Hydrocarbons containing 8 - 15 % of N. Hexane	110-54-3	>90.0 %

Health Hazard Information

Health Effects

Swallowed:	Moderately Toxic.
Eye:	May cause pain, may irritate eyes.
Skin:	Prolonged contact may cause flaking or drying of skin.
Inhaled:	Irritating to respiratory tract. Toxic by inhalation, prolonged exposure may cause somnolence and narcosis

First Aid

Swallowed:	Do not induce vomiting, give plenty of water & seek medical attention.
Eye:	Immediately hold open eyes open and flush with water continuously for at least 15 minutes. Seek medical attention.
Skin:	Remove all contaminated clothing and wash affected area with plenty of water and soap and seek medical attention.
Inhaled:	Remove from further exposure and apply artificial respiration if not breathing. Seek medical attention.
<u>Advice to doctor</u>	Treat symptomatically.

Precaution for Use

<u>Exposure Limits</u>	TLV:- n-hexane 50ppm, 180mg/m ³ TWA,ACGIH. TLV:- other isomers 500ppm 180mg/m ³ TWA,ACGIH
<u>Ventilation</u>	If above T.W.A. Extra spark arrested ventilation is required.
<u>Personal Protection</u>	No Smoking, eating or drinking during handling. Avoid any contact with the product. Wear safety goggles, suitable breathing apparatus and gloves
<u>Flammability</u>	The product is highly flammable. Isolate from sources of heat, flames or sparks. Take Precautions against static electricity discharge.

Safe Handling Information

Storage & Transport

Product is a class 3 Flammable. Store indoors in a dry well ventilated area away from oxidising agent.

Spills & Disposal

Wear protective clothing, goggles and protective gloves. wear a suitable respiratory device if spillage is in a confined space. Extinguish or remove all sources of ignition.

Shut off source of leak if safe to do so. Dyke and contain spill with sand or earth. Allow to evaporate if conditions permit

Fire & Explosive Hazard

Highly Flammable, extinguish with carbon dioxide dry chemical or foam. Explosive air vapour mixture may form.

Keep containers cool by spraying with water to prevent pressure build-up and drums bursting.

Other Information

The information presented herein is true and accurate to the best of our knowledge, but without guarantee unless explicitly given. Since the conditions of use are beyond our control, we disclaim any liability including for patent infringement incurred in connection with the use of these products, data or suggestions.

Contact Point:

Glyn McDonald
Sierra (AUST) PTY. LTD.
17 Delta Street
GEEBUNG QLD 4034

Phone: (07) 3216 5099

Fax: (07) 3216 5199

Signed:

_____ **Date of issue: September 2007**
Glyn McDonald

Note:

This issue supersedes and replaces all previous issues.