

# MATERIAL SAFETY DATA SHEET

## Sierra UB 702

### Identification

Product Name "Sierra UB 702 Anti corrosive Coating"

UN Number:	1263
Dangerous Goods Class:	3.2
Poisons Schedule:	5
Hazchem Code:	3YE
Packaging Group:	II

Shipping Name:

Flammable Liquids N.O.S. 1.f.p.

N/A = Not applicable

Use: Anti Corrosive Coating to Metals

### **Physical Description/Properties**

Appearance:	Black thixotropic liquid
Flash Point: (Deg.F)	<100
Boiling Point: (Deg.F)	<325
Specific Gravity:	1.08 (+-).02
Solubility in Water:	immiscible
Flammability Limits:	flammable LEL: 1.2 5 V/V UEL: 7.5% V/V
pH as is	N/A

### **Ingredients**

Ingredient	Percentages
Mineral Clay	Low
Bituminous Paint	Medium
Liquid Hydrocarbons	Medium
Technical Wax	Low
Inhibitors	Low

## Health Hazard Information

### **Health Effects**

Swallowed:	Moderately toxic.
Eye:	Could cause pain, may result in permanent injury to eyes.
Skin:	Prolonged contact may cause flaking or drying of skin.
Inhaled:	Slow narcosis at high concentrations

### **First Aid**

Swallowed:	Do not induce vomiting unless instructed by doctor seek medical attention.
Eye:	Immediately hold open eyes open and flush with water continuously for at least 15 minutes. Seek medical attention.
Skin:	Remove all contaminated clothing and wash affected area with plenty of water and soap and seek medical attention.
Inhaled:	Remove from further exposure and apply artificial respiration if not breathing. Seek medical attention.
<u>Advice to doctor</u>	Treat symptomatically.

## Precaution for Use

<u>Exposure Limits</u>	TLV:100 ppm, 180mg/m3 TWA ACGIH
<u>Ventilation</u>	Extra ventilation may be required to maintain air levels below the exposure limit.
<u>Personal Protection</u> and	No Smoking, eating or drinking during handling. Avoid any contact with the product. Wear safety goggles, suitable breathing apparatus gloves
<u>Flammability</u>	The product is highly flammable.

---

## Safe Handling Information

---

### Storage & Transport

Product is a class 3 Flammable. Store indoors in a dry well ventilated area, away from ignition sources.

### Spills & Disposal

with inert

Wear protective clothing, goggles and protective gloves. wear a suitable respiratory device if spillage is in a confined space, remove from all sources of ignition. Absorb

material and transfer into drums.

Contact local Waste Disposal Authority before you dispose of material. Observe all Federal, State and local regulations.

### Fire & Explosive Hazard

Flammable, extinguish with carbon dioxide dry chemical or halogen (BCF).

Keep containers cool by spraying with water to prevent pressure build-up and drums bursting.

### ***Other Information***

The information presented herein is true and accurate to the best of our knowledge, but without guarantee unless explicitly given. Since the conditions of use are beyond our control, we disclaim any liability including for patent infringement incurred in connection with the use of these products, data or suggestions.

Contact Point:

Glyn Mc Donald  
Sierra (AUST) PTY. LTD.  
17 Delta Street  
GEEBUNG QLD 4034

Phone: (07) 3216 5099

Fax: (07) 3216 5199

Note:

Dated Nov 2009.